

Appln No. 09/522,185

Amdt date June 15, 2004

Reply to Office action of March 31, 2004


**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A signal processing system, comprising:

a voice exchange ~~capable of~~ for exchanging voice signals between a network line and a packet based network; and

 a full duplex data exchange ~~capable of~~ for exchanging data signals from the network line with ~~demodulated~~ data signals from the packet based network, wherein the full duplex data exchange demodulates the data signals from the network line and outputs the demodulated data signals to the packet based network, and wherein the full duplex data exchange remodulates the demodulated data signals from the packet based network and outputs the remodulated data signals to the network line.

2. (Original) The signal processing system of claim 1 further comprising a call discriminator capable of discriminating between the voice signals and the data signals from the network line,

the voice exchange being enabled for the voice signals and the data exchange being enabled for the data signals.

3. (Original) The signal processing system of claim 1 wherein the data signals from the network line are modulated by

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

a voiceband carrier, and the data exchange comprises a data pump capable of demodulating the data signals from the network line for transmission on the packet based network and remodulating the data signals from the packet based network with the voiceband carrier for transmission on the network line.

4. (Original) The signal processing system of claim 3 wherein the data exchange comprises a jitter buffer capable of receiving packets of the data signals of varying delay from the packet based network and compensating for the delay variation of the data signal packets.

5. (Original) The signal processing system of claim 4 wherein the jitter buffer outputs an isochronous stream of the received data signals.

6. (Original) The signal processing system of claim 4 wherein the data pump transmits the received data signals to the network line at a transmit rate.

7. (Original) The signal processing system of claim 6 wherein the jitter buffer compensates for the delay variation of the data signal packets by holding a number of the received data signals, and wherein the data exchange further comprises a clock synchronizer which adaptively adjusts the transmit rate of the data pump in response the number of the received data signals in the jitter buffer.

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

8. (Original) The signal processing system of claim 6 wherein the jitter buffer compensates for the delay variation of the data signal packets by holding a number of the received data signals, and wherein the data exchange further comprises spoof logic which provides spoof data to the data pump when the number of the received data signals held in the jitter buffer is below a threshold.

9. (Original) The signal processing system of claim 1 wherein the voice exchange comprises a jitter buffer capable of receiving packets of the voice signals of varying delay from the packet based network and compensating for the delay variation of the voice signal packets.

10. (Original) The signal processing system of claim 9 wherein the jitter buffer outputs an isochronous stream of the received voice signals.

11. (Original) The signal processing system of claim 9 wherein the jitter buffer comprises a voice queue which buffers the received voice signals for a holding time, and a voice synchronizer which adaptively adjusts the holding time of the voice queue.

12. (Original) The signal processing system of claim 11 further comprising a tone exchange capable of exchanging DTMF signals between the network line and the packet based network, the DTMF exchange comprising a DTMF queue capable of buffering

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

packets of the DTMF signals from the packet based network, and a tone generator which generates a DTMF tone responsive to the buffered DMTF signals, the DMTF queue outputting a signal to the voice synchronizer to suppress the buffered voice signals when the DTMF signals are in the DTMF queue.

13. (Original) The signal processing system of claim 1 wherein the voice exchange comprises a voice decoder capable of decoding packets of the voice signals from the packet based network for transmission to the network line, a voice activity detector which detects the voice signals without speech, and a comfort noise generator which inserts comfort noise in place of the voice signals without speech.

14. (Original) The signal processing system of claim 13 wherein the voice exchange further comprises a comfort noise estimator which generates comfort noise parameters from at least a portion of the voice signals without speech, the comfort noise generator being responsive to the comfort noise parameters.

15. (Original) The signal processing system of claim 1 wherein the voice exchange comprises a voice decoder capable of decoding packets of the voice signals from the packet based network for transmission to the network line, a voice activity detector which detects lost voice signals, and a lost packet recovery engine which processes the voice signals to compensate for the lost voice signals.

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

16. (Original) The signal processing system of claim 1 wherein the voice exchange comprises a voice encoder capable of encoding the voice signals from the network line for transmission on the packet based network, and a voice activity detector which suppresses the voice signals without speech.

17. (Previously Presented) The signal processing system of claim 16 wherein the voice exchange further comprises a comfort noise estimator which generates comfort noise parameters when the voice activity detector suppresses the voice signals without speech.

18. (Original) The signal processing system of claim 1 wherein the voice exchange further comprises a decoder capable of decoding packets of the voice signals from the packet based network, and an echo canceller capable of cancelling decoded voice signal echos on incoming voice signals from the network line.

19. (Previously Presented) The signal processing system of claim 18 wherein the voice exchange further comprises a non-linear processor which mutes the incoming voice signals when the incoming voice signals do not comprise speech and the echo canceller detects the decoded voice signals with speech.

20. (Original) The signal processing system of claim 1 wherein the voice exchange comprises a voice encoder capable of

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

encoding the voice signals from the network line into voice signal packets for the packet based network.

21. (Previously Presented) The signal processing system of claim 20 wherein the voice exchange further comprises a tone exchange comprising a DTMF detector capable of detecting a DTMF signal from the network line and generating a DTMF packet for the packet based network in response to the DTMF signal, the DTMF detector muting the voice signal packets when a DTMF signal is detected.

22. (Original) The signal processing system of claim 1 further comprising a fax exchange capable of exchanging fax signals from the network line with demodulated fax signals from the packet based network

23. (Original) The signal processing system of claim 22 wherein the fax signals from the network line are modulated by a voiceband carrier, and the fax exchange comprises a data pump capable of demodulating the fax signals from the network line for transmission on the packet based network, and remodulating the fax signals from the packet based network with the voiceband carrier for transmission on the network line.

24. (Original) The signal processing system of claim 22 wherein the call discriminator is capable of discriminating the fax signals from the network line, the fax exchange being enabled for the fax signals.

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

25. (Original) The signal processing system of claim 1 wherein the data exchange comprises a rate synchronizer capable of receiving data rate codes from the packet based network and setting a data rate of a telephony device coupled to the network line in response to the received data rate codes.

26. (Currently Amended) A signal processing system, comprising:

a voice exchange ~~capable of~~ for exchanging voice signals between a first telephony device and a packet based network;

a full duplex data exchange ~~capable of~~ for exchanging data signals from a second telephony device with demodulated data signals from the packet based network, wherein the full duplex data exchange demodulates the data signals from the first telephony device and outputs the demodulated data signals to the packet based network, and wherein the full duplex data exchange remodulates the demodulated data signals from the packet based network and outputs the remodulated data signals to the first telephony device; and

a call discriminator which selectively enables at least one of the voice exchange and the data exchange.

27. (Original) The signal processing system of claim 26 wherein the call discriminator is capable of discriminating between the voice signals and the data signals, the voice

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

exchange being enabled for the voice signals and the data exchange being enabled for the data signals.

28. (Original) The signal processing system of claim 26 wherein the data signals from the second telephony device are modulated by a voiceband carrier, and the data exchange comprises a data pump capable of demodulating the data signals from the second telephony device for transmission on the packet based network and remodulating the data signals from the packet based network with the voiceband carrier for transmission to the second telephony device.

29. (Original) The signal processing system of claim 28 wherein the data exchange comprises a jitter buffer capable of receiving packets of the data signals of varying delay from the packet based network and compensating for the delay variation of the data signal packets.

30. (Original) The signal processing system of claim 29 wherein the jitter buffer outputs an isochronous stream of the received data signals.

31. (Original) The signal processing system of claim 29 wherein the data pump is capable of transmitting the received data signals to the second telephony device at a transmit rate.

32. (Original) The signal processing system of claim 31 wherein the jitter buffer compensates for the delay variation



**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

of the data signal packets by holding a number of the received data signals, and wherein the data exchange further comprises a clock synchronizer which adaptively adjusts the transmit rate of the data pump in response the number of the received data signals in the jitter buffer.

33. (Original) The signal processing system of claim 31 wherein the jitter buffer compensates for the delay variation of the data signal packets by holding a number of the received data signals, and wherein the data exchange further comprises spoof logic which provides spoof data to the data pump when the number of the received data signals held in the jitter buffer is below a threshold.

34. (Original) The signal processing system of claim 26 wherein the voice exchange comprises a jitter buffer capable of receiving packets of the voice signals of varying delay from the packet based network and compensating for the delay variation of the voice signal packets.

35. (Original) The signal processing system of claim 34 wherein the jitter buffer outputs an isochronous stream of the received voice signals.

36. (Original) The signal processing system of claim 34 wherein the jitter buffer comprises a voice queue which buffers the received voice signals for a holding time, and a

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

voice synchronizer which adaptively adjusts the holding time of the voice queue.

37. (Original) The signal processing system of claim 36 further comprising a tone exchange capable of exchanging DTMF signals between the first telephony device and the packet based network, the DTMF exchange comprising a DTMF queue capable of buffering packets of the DTMF signals from the packet based network, and a tone generator which generates a DTMF tone responsive to the buffered DMTF signals, the DMTF queue outputting a signal to the voice synchronizer to suppress the buffered voice signals when the DTMF signals are in the DTMF queue.

38. (Original) The signal processing system of claim 26 wherein the voice exchange comprises a voice decoder capable of decoding packets of the voice signals from the packet based network for transmission to the first telephony device, a voice activity detector which detects the voice signals without speech, and a comfort noise generator which inserts comfort noise in place of the voice signals without speech.

39. (Original) The signal processing system of claim 38 wherein the voice exchange further comprises a comfort noise estimator which generates comfort noise parameters from at least a portion of the voice signals without speech, the comfort noise generator being responsive to the comfort noise parameters.

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

40. (Original) The signal processing system of claim 26 wherein the voice exchange comprises a voice decoder capable of decoding packets of the voice signals from the packet based network for transmission to the first telephony device, a voice activity detector which detects lost voice signals, and a lost packet recovery engine which processes the voice signals to compensate for the lost voice signals.

41. (Original) The signal processing system of claim 26 wherein the voice exchange comprises a voice encoder capable of encoding the voice signals from the first telephony device for transmission on the packet based network, and a voice activity detector which suppresses the voice signals without speech.

42. (Original) The signal processing system of claim 41 wherein the voice exchange further comprises a comfort noise estimator which generates comfort noise parameters when the voice activity detector suppresses the voice signals without speech.

43. (Original) The signal processing system of claim 26 wherein the voice exchange further comprises a decoder capable of decoding packets of the voice signals from the packet based network, and an echo canceller capable of cancelling decoded voice signal echos on incoming voice signals from the first telephony device.

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

44. (Original) The signal processing system of claim 43 wherein the voice exchange further comprises a non-linear processor which mutes the incoming voice signals when the incoming voice signals do not comprise speech and the echo canceller detects the decoded voice signals with speech.

45. (Original) The signal processing system of claim 26 wherein the voice exchange comprises a voice encoder capable of encoding the voice signals from the first telephony device into voice signal packets for the packet based network.

46. (Original) The signal processing system of claim 45 further comprising a tone exchange comprising a DTMF detector capable of detecting a DTMF signal from the first telephony device and generating a DTMF packet for the packet based network in response to the DTMF signal, the DTMF detector muting the voice signal packets when a DTMF signal is detected.

47. (Original) The signal processing system of claim 26 further comprising a fax exchange capable of exchanging fax signals from a third telephony device with demodulated fax signals from the packet based network, wherein the call discriminator selectively enables the fax exchange.

48. (Original) The signal processing system of claim 47 wherein the fax signals from the third telephony device are modulated by a voiceband carrier, and the fax exchange comprises a data pump capable of demodulating the fax signals from the

Appln No. 09/522,185

Amdt date June 15, 2004

Reply to Office action of March 31, 2004

third telephony device for transmission on the packet based network, and remodulating the demodulated fax signals from the packet based network with the voiceband carrier for transmission to the third telephony.

49. (Currently Amended) A method of processing signals, comprising:

exchanging voice signals between a network line and a packet based network;

demodulating data signals from the network line for inputting to the packet based network;

remodulating the demodulated data signals from the packet based network for inputting to the network line; and

simultaneously exchanging the remodulated data signals from the network line with demodulated data signals from the packet based network.

50. (Original) The method of claim 49 further comprising discriminating between the voice signals and the data signals from the network line, and selectively invoking at least one of the voice signal exchange and the data signal exchange based on said discrimination.

51. (Original) The method of claim 49 wherein the data signals from the network line are modulated by a voiceband carrier, and the data exchange comprises demodulating the data signals from the network line for transmission on the packet based network and remodulating the data signals from the packet

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

based network with the voiceband carrier for transmission on the network line.

52. (Original) The method of claim 49 wherein the voice exchange further comprises receiving packets of the signals of varying delay from the packet based network, and compensating for the delay variation of the signal packets.

53. (Original) The method of claim 52 wherein the signal packet compensation comprises generating an isochronous stream of the received signals.

54. (Original) The method of claim 52 wherein the signal packet compensation comprises adaptively buffering the received signals.

55. (Original) The method of claim 49 wherein the voice signal exchange comprises receiving packets of the voice signals from the packet based network, identifying the received voice signals without speech, and inserting comfort noise in place of the identified voice signals without speech.

56. (Original) The method of claim 55 wherein the comfort noise insertion comprises estimating comfort noise in response to at least a portion of the received voice signals without speech.

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

57. (Original) The method of claim 49 wherein the voice signal exchange comprises receiving packets of the voice signals from the packet based network, detecting lost voice signals, decoding the received voice signals for transmission to the network line, and processing the decoded voice signals to compensate for the lost voice signals.

58. (Original) The method of claim 49 further comprising exchanging DTMF signals between the network line and the packet based network.

59. (Original) The method of claim 58 wherein the DTMF signal exchange comprises receiving packets of the DTMF signals from the packet based network, and generating at least one DTMF tone from the DTMF signals.

60. (Original) The method of claim 59 wherein the voice signal exchange comprises receiving packets of the voice signals from the packet based network, and the DTMF signal exchange further comprises muting the received voice signals when the DTMF signal packets are received.

61. (Original) The method of claim 49 wherein the voice signal exchange comprises decoding packets of the voice signals from the packet based network, receiving voice signals from the network line and canceling decoded voice signal echos on the received voice signals.

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

62. (Original) The method of claim 49 wherein the voice signal exchange comprises encoding the voice signals from the network line into voice signal packets for transmission on the packet based network.

63. (Original) The method of claim 62 further comprising exchanging DTMF signals between the network line and the packet based network, wherein the DTMF signal exchange comprises detecting DTMF signals from the network line, generating DTMF signal packets for the packet based network in response to the DTMF signals, and muting the voice signal packets when the DTMF signals are detected.

64. (Original) The method of claim 49 wherein the voice signal exchange comprises receiving the voice signals from the network line and suppressing the received voice signals when the received voice signals do not comprise speech.

65. (Original) The method of claim 64 wherein the suppression of the received voice signals comprises generating comfort noise parameters in place thereof.

66. (Original) The method of claim 49 further comprising exchanging fax signals from the network line with demodulated fax signals from the packet based network

67. (Original) The method of claim 66 wherein the fax signals from the network line are modulated by a voiceband



**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

carrier, and the fax exchange comprises demodulating the fax signals from the network line for transmission on the packet based network and remodulating the fax signals from the packet based network with the voiceband carrier for transmission on the network line.

68. (Original) The method of claim 67 wherein the signal discrimination further comprises discriminating the fax signals from the network line, and selectively invoking the fax exchange based on said discrimination.

69. (Original) The method of claim 49 wherein the data signal exchange further comprises receiving packets of the data signals from the packet based network, holding a number of the received data signals in a buffer, and generating spoof data when the number of the data signals in the buffer is below a threshold.

70. (Original) The method of claim 49 wherein the data signal exchange further comprises receiving packets of the data signals from the packet based network, holding a number of the received data signals in a buffer, transmitting the buffered data signals to the network line at a transmit rate, and adaptively adjusting the transmit rate in response the number of the received data signals in the buffer.

71. (Original) The method of claim 49 wherein the data signal exchange further comprises receiving data rate codes from

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

the packet based network, and setting a data rate of a telephony device coupled to the network line in response to the received data rate codes.

72. (Original) The method of claim 49 wherein the network line comprises a circuit switched network line.

73. (Original) The method of claim 72 wherein the circuit switched network line comprises a public switching telephone network line.

74. (Currently Amended) A method of processing signals, comprising:

exchanging voice signals between a first telephony device and a packet based network;

demodulating data signals from the first telephony device for inputting to the packet based network;

remodulating the demodulated data signals from the packet based network;

simultaneously exchanging the remodulated data signals from a second telephony device with demodulated data signals from the packet based network; and

discriminating between the voice signals and the data signals, and invoking at least one of the voice exchange and the data exchange based on said discrimination.

75. (Original) The method of claim 74 wherein the data signals from the second telephony device are modulated by a

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

voiceband carrier, and the data exchange comprises demodulating the data signals from the second telephony device for transmission on the packet based network and remodulating the data signals from the packet based network with the voiceband carrier for transmission to the second telephony device.

76. (Original) The method of claim 74 further comprising receiving packets of the signals of varying delay from the packet based network, and compensating for the delay variation of the signal packets.

77. (Original) The method of claim 76 wherein the signal packet compensation comprises generating an isochronous stream of the received signals.

78. (Original) The method of claim 76 wherein the signal packet compensation comprises adaptively buffering the received signals.

79. (Original) The method of claim 74 wherein the voice signal exchange comprises receiving packets of the voice signals from the packet based network, identifying the received voice signals without speech, and inserting comfort noise in place of the identified voice signals without speech.

80. (Original) The method of claim 79 wherein the comfort noise insertion comprises estimating comfort noise in

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

response to at least a portion of the received voice signals without speech.

81. (Original) The method of claim 74 wherein the voice signal exchange comprises receiving packets of the voice signals from the packet based network, detecting lost voice signals, decoding the received voice signals for transmission to the first telephony device, and processing the decoded voice signals to compensate for the lost voice signals.

82. (Original) The method of claim 74 wherein the signal discrimination further comprises discriminating between the voice signals, the data signals, and DTMF signals, and further comprising exchanging the discriminated DTMF signals between the first telephony device and the packet based network.

83. (Original) The method of claim 82 wherein the DTMF signal exchange comprises receiving packets of the DTMF signals from the packet based network, and generating at least one DTMF tone from the DTMF signals.

84. (Original) The method of claim 83 wherein the voice signal exchange comprises receiving packets of the voice signals from the packet based network, and the DTMF signal exchange further comprises muting the received voice signals when the DTMF signal packets are received.

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

85. (Original) The method of claim 74 wherein the voice signal exchange comprises decoding packets of the voice signals from the packet based network, receiving voice signals from the first telephony device and canceling decoded voice signal echos on the received voice signals.

86. (Original) The method of claim 74 wherein the voice signal exchange comprises encoding the voice signals from the first telephony device into voice signal packets for transmission on the packet based network.

87. (Original) The method of claim 86 further comprising exchanging the DTMF signals between the first telephony device and the packet based network, wherein the DTMF signal exchange comprises detecting DTMF signals from the first telephony device, generating DTMF signal packets for the packet based network in response to the DTMF signals, and muting the voice signal packets when the DTMF signals are detected.

88. (Original) The method of claim 74 wherein the voice signal exchange comprises receiving the voice signals from the first telephony device and suppressing the received voice signals when the received voice signals do not comprise speech.

89. (Original) The method of claim 88 wherein the suppression of the received voice signals comprises generating comfort noise parameters in place thereof.

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

90. (Original) The method of claim 74 wherein further comprising exchanging fax signals from a third telephony device with demodulated fax signals from the packet based network, wherein the signal discrimination comprises selectively invoking the fax exchange.

91. (Original) The method of claim 90 wherein the fax signals from the third telephony device are modulated by a voiceband carrier, and the fax exchange comprises a data pump capable of demodulating the fax signals from the third telephony device for transmission on the packet based network, and remodulating the fax signals from the packet based network with the voiceband carrier for transmission to the third telephony device.

92. (Original) The method of claim 74 wherein the data signal exchange further comprises receiving packets of the data signals from the packet based network, holding a number of the received data signals in a buffer, and spoofing the second telephony device when the number of the data signals in the buffer is below a threshold.

93. (Original) The method of claim 74 wherein the data signal exchange further comprises receiving packets of the data signals from the packet based network, holding a number of the received data signals in a buffer, transmitting the buffered data signals to the second telephony device at a transmit rate,

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

and adaptively adjusting the transmit rate in response the number of the received data signals in the buffer.

94. (Original) The method of claim 74 wherein the data signal exchange further comprises receiving data rate codes from the packet based network, and setting a data rate of the second telephony device in response to the received data rate codes.

95. - 174. (Cancelled)

---